

CERTIFICATE

Issued to:
Applicant:
AEC ILLUMINAZIONE Srl
Via A. Righi, 4 -
Z.I. Castelnuovo
52010 Subbiano (AR), Italy

Licensee:
AEC ILLUMINAZIONE Srl
Via A. Righi, 4 -
Z.I. Castelnuovo
52010 Subbiano (AR), Italy

Product : Luminaires for road and street lighting
Trade name(s) : AEC ILLUMINAZIONE
Type(s)/model(s) : Series COMPASS 2

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard EN 60598-2-3:2003, EN 60598-2-3:2003/A1:2011, EN 60598-1:2015, EN 60598-1:2015/AC:2016, EN 60598-1:2015/AC:2015 and EN 60598-1:2015/A1:2018
- an inspection of the production location according to CENELEC Operational Document CIG 021
- a certification agreement with the number 3504208

DEKRA hereby grants the right to use the ENEC certification mark.


Compliance with the requirements of this Standard carries a presumption of conformity with the essential safety requirements of the Low voltage directive (LVD) 2014/35/EU.

The ENEC certification mark may be applied to the product as specified in this certificate for the duration of the ENEC certification agreement and under the conditions of the ENEC certification agreement.

This certificate is issued on 25 January 2019 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 81-107154

DEKRA Certification B.V.



B.T.M. Holtus
Managing Director



JMg Marggraf
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE
DUTCH ACCREDITATION
COUNCIL



SPECIFICATION OF THE CERTIFIED PRODUCT**Product data**

Product	: Luminaires for road and street lighting
Trade name(s)	: AEC ILLUMINAZIONE
Type(s)/model(s)	: COMPASS 2
Supply voltage	: 220-240 V
Rated frequency	: 50/60 Hz
Protection class	: Class I
IP degree	: IP66
Rated input	: Max 192 W
Ambient temperature	: 50 °C

TESTS**Test requirements**

EN 60598-2-3:2003
EN 60598-2-3:2003/A1:2011
EN 60598-1:2015
EN 60598-1:2015/AC:2016
EN 60598-1:2015/AC:2015
EN 60598-1:2015/A1:2018

Test result

The test results are laid down in DEKRA test file 350621700.

Additional information

Dekra test report No. 3506217.51 is laid down in Dekra test file 350621700. It contains both test results and critical component list

For a complete list of models/series, see table on the annex of this certificate.

Conclusion

The examination proved that all requirements were met.

Factory location

AEC ILLUMINAZIONE Srl
Via A. Righi, 4 -
Z.I. Castelnuovo
52010 Subbiano (AR), Italy

8 LED

Series / Models	Supply voltage V	Hz	P max W	Protection class	N° Led	Iout max mA	IP degree	t _a
COMPASS 2 PC2xywwzaaaa011_bb v.ch*****	220-240	50/60	24 30	Class I	8	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa021_bb v.ch*****	220-240	50/60	48 60	Class I	16	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa031_bb v.ch*****	220-240	50/60	72 90	Class I	24	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa041_bb v.ch*****	220-240	50/60	96 120	Class I	32	450 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa051_bb v.ch*****	220-240	50/60	120 150	Class I	40	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa061_bb v.ch*****	220-240	50/60	144 180	Class I	48	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa071_bb v.ch*****	220-240	50/60	168 189	Class I	56	400 450	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa081_bb v.ch*****	220-240	50/60	192	Class I	64	400	IP66 IK08	50 °C

LEGEND

x	Fixing Type	B= post-top / bracket attachment (TB / BR) T= post-top / bracket attachment (T0050-AM) M = Suspended on bracket (S) S = Suspension wires (TS)
y	Revision	0,1,2,...9,A,B,C,...Z
ww	Optic Type	0D = STU-M 0E = STU-S 26 = STU-W 0P = HPO00 0Q = HPO01 ww= Other type of optic
z	Colour temperature	3 = 3000 K 4 = 4000 K 5 = 5000 K 6 = 5700 K z = Other temperature ≤ 5700 K available
aaaa	LED current	0400 = 400 mA 0500 = 500 mA aaaa = other current ≤ 500 mA
bb	Finishing equipment	Stands for any letter or number indicating different colors of the luminaire for marketing purpose only and no impact on safety related constructions and critical components.
c	Dimming version	1 = DA 2 = DAC 3 = DB-D 4 = DB-I 5 = DB-D/T 6 = DB-I/T 7 = DIM-REG 9 = 1-10V EXT A = DALI EXT E = NEMA SOCKET G = WL H = WL-A I = ZHAGA c = Other type of control
h	Protection	0 = With SPD 1 = With TMOV 2 = Without protection device
* (5 digit)	Code for internal use of the manufacturer to handle special versions such as pre-mounted supply cable, connecting connectors, or led manufacturer	

6 LED

Series / Models	Supply voltage V	Hz	P max W	Protection class	N° Led	Iout max mA	IP degree	t _a
COMPASS 2 PC2xywwzaaaa011_bb v.ch*****	220-240	50/60	18 23	Class I	6	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa021_bb v.ch*****	220-240	50/60	36 45	Class I	12	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa031_bb v.ch*****	220-240	50/60	54 68	Class I	18	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa041_bb v.ch*****	220-240	50/60	72 90	Class I	24	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa051_bb v.ch*****	220-240	50/60	90 113	Class I	30	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa061_bb v.ch*****	220-240	50/60	108 135	Class I	36	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa071_bb v.ch*****	220-240	50/60	126 158	Class I	42	400 500	IP66 IK08	50 °C
COMPASS 2 PC2xywwzaaaa081_bb v.ch*****	220-240	50/60	144 180	Class I	48	400 500	IP66 IK08	50 °C

LEGEND

x	Fixing Type	B = post-top / bracket attachment (TP / BR) T = post-top / wall attachment (TP-AM) M = Suspended on bracket (S) S = Suspension wires (TS)
y	Revision	0,1,2,...9,A,B,C,...Z
ww	Optic Type	OL = STA OM = STA1 ON = STW-15 ww = Other type of optic
z	Colour temperature	3 = 3000 K 4 = 4000 K 5 = 5000 K 6 = 5700 K z = Other temperature ≤ 5700 K available
aaaa	LED current	0400 = 400 mA 0500 = 500 mA aaaa = other current ≤ 500 mA
bb	Finishing equipment	Stands for any letter or number indicating different colors of the luminaire for marketing purpose only and no impact on safety related constructions and critical components.
c	Dimming version	0 = No dimming 1 = DA 2 = DAC 3 = DB-D 4 = DB-I 5 = DB-D/T 6 = DB-I/T 7 = DIM-REG 9 = 1-10V EXT A = DALI EXT E = NEMA SOCKET G = WL Wireless H = WL-A I = ZHAGA c = Other type of control

h	Protection	0 = with SPD 1 = with TMOV 2 = without protection device
* (5 digit)	Code for internal use of the manufacturer to handle special versions such as pre-mounted supply cable, connecting connectors, or led manufacturer	