



MX PRO 1

MAIN CHARACTERISTICS

Applications	Street and architectural lighting.
Optic	<p>STE-M/S: Asymmetrical optic for suburban street lighting. STU-M/S: Asymmetrical optic for street, urban and cycle-path lighting. STW: Asymmetrical optic for wide urban and suburban road lighting, specific for wet asphalts. SV: Asymmetrical optic for very narrow urban streets or highway entrance/exit turns. S05/S07: Asymmetrical optic for street, urban and green areas lighting. STA: Asymmetrical optic for wide urban road and cycle-path lighting. AS: Asymmetrical optics for floodlighting. Colour temperature: 4000K, 3000K, 2700K, 2200K (others in option) CRI ≥ 70 LOR= 100%, DLOR= 100%, ULOR= 0% Photobiological safety class: EXEMPT GROUP LED source efficiency: 185 lm/W @ 140mA, Tj=85°C, 4000K</p>
Insulation class	II, I
Protection degree	IP66/IP67 IK09 total
Dimensions	See the drawing
Weight	max 6kg (without fixing flange)
Exposed surface	Side: 0.026m ² – Top: 0.12m ² SCx 0.139 m ²
Mounting	Mounting with integrated flange
Tilt Angle	± 90°
LED Modules	Removable / Replaceable.
Gear tray	Removable.
Operating temp.	-40°C / +50°C
Storage temp	-40°C / +80°C
Main reference standards	EN 60598-1, EN 60598-2-3, EN 60598-2-5, IEC 62471, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3



ELECTRICAL CHARACTERISTICS

Rated voltage	220÷240V 50/60Hz (Standard tolerance +/-10%, other voltages and tolerances upon request)
Power factor	>0,95 (at full load - F, DA, DAC)
Mains connection	Terminal block for cables max section 4mm ²
Surge protection	Up to 12kV With SPD: CL.II: 10kV / 10kV CM/DM CL.I: 12kV / 10kV CM/DM Without SPD: CL.II: 10kV / 6kV CM/DM CL.I: 10kV / 6kV CM/DM
SPD (optional)	12kV-10kA, type 2+3, with LED signal and thermo fuse to disconnect load at the end of life.
Control system (options)	<p>F: Fixed power not dimmable. DA: Automatic dimming (virtual midnight) with default profile. DAC: Custom DA profile. FLC: Constant light flux. DALI: Digital dimming interface DALI. NEMA: Socket 7 pin (ANSI C136.41). ZHAGA: Socket 4 pin (ZHAGA Book 18).</p>
Optical unit lifetime (Tq=25°C)	>100.000hr L90B10 >100.000hr L90, TM-21

MATERIALS

Fixing	AISI 304 stainless steel
Lower frame	Die-cast aluminum UNI EN1706 powder painted.
Upper canopy	
Closure hook	Extruded aluminium with stainless steel spring.
Optic	99.85% aluminum with a surface finish in 99.95% with vacuum-sealed deposition. Aluminum grade class A+ (DIN EN 16268)
Screen	Flat tempered glass, 4mm thickness high transparency.
Cable gland	Metallic M20x1.5 - IP68
Gasket	Polyurethane
Colour	Graphite - Cod. 01

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)	
MX PRO 1 5P5 7040.060-1M	STE-M STU-M STW SV	60	1730	11.9	145.3	1847	9.4	
MX PRO 1 5P5 7040.060-2M			3480	23	151.3	3694	18.8	
MX PRO 1 5P5 7040.060-3M			5230	33.8	154.7	5541	28.2	
MX PRO 1 5P5 7040.060-4M			7030	43.4	161.9	7387	37.6	
MX PRO 1 5P5 7040.100-1M		100	2830	19.1	148.1	3023	16	
MX PRO 1 5P5 7040.100-2M			5670	37.4	151.6	6046	31.9	
MX PRO 1 5P5 7040.100-3M			8500	54.8	155.1	9069	47.9	
MX PRO 1 5P5 7040.100-4M			11320	72	157.2	12092	63.8	
MX PRO 1 5P5 7040.140-1M		140	3920	26.8	146.2	4150	22.7	
MX PRO 1 5P5 7040.140-2M			7770	52.3	148.5	8299	45.4	
MX PRO 1 5P5 7040.140-3M			11620	76.7	151.4	12449	68	
MX PRO 1 5P5 7040.140-4M			15300	102	150	16598	90.7	
MX PRO 1 5P5 7040.180-1M		180	4900	34.8	140.8	5227	29.6	
MX PRO 1 5P5 7040.180-2M			9680	67.7	142.9	10453	59.1	
MX PRO 1 5P5 7040.180-3M			14450	100	144.5	15680	88.7	
MX PRO 1 5P5 7040.180-4M			19030	132	144.1	20906	118	
MX PRO 1 5P5 7040.060-1M		S05 S07 STA STE-S STU-S	60	1690	11.9	142	1847	9.4
MX PRO 1 5P5 7040.060-2M				3400	23	147.8	3694	18.8
MX PRO 1 5P5 7040.060-3M				5100	33.8	150.8	5541	28.2
MX PRO 1 5P5 7040.060-4M				6870	43.4	158.2	7387	37.6
MX PRO 1 5P5 7040.100-1M	100		2770	19.1	145	3023	16	
MX PRO 1 5P5 7040.100-2M			5540	37.4	148.1	6046	31.9	
MX PRO 1 5P5 7040.100-3M			8310	54.8	151.6	9069	47.9	
MX PRO 1 5P5 7040.100-4M			11060	72	153.6	12092	63.8	
MX PRO 1 5P5 7040.140-1M	140		3820	26.8	142.5	4150	22.7	
MX PRO 1 5P5 7040.140-2M			7600	52.3	145.3	8299	45.4	
MX PRO 1 5P5 7040.140-3M			11370	76.7	148.2	12449	68	
MX PRO 1 5P5 7040.140-4M			14950	102	146.5	16598	90.7	

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7040.180-1M			4770	34.8	137	5227	29.6
MX PRO 1 5P5 7040.180-2M		180	9470	67.7	139.8	10453	59.1
MX PRO 1 5P5 7040.180-3M			14140	100	141.4	15680	88.7
MX PRO 1 5P5 7040.180-4M			18590	132	140.8	20906	118
MX PRO 1 5P5 7040.060-1M			1730	11.9	145.3	1847	9.4
MX PRO 1 5P5 7040.060-2M		60	3460	23	150.4	3694	18.8
MX PRO 1 5P5 7040.060-3M			5210	33.8	154.1	5541	28.2
MX PRO 1 5P5 7040.060-4M			7010	43.4	161.5	7387	37.6
MX PRO 1 5P5 7040.100-1M			2830	19.1	148.1	3023	16
MX PRO 1 5P5 7040.100-2M		100	5650	37.4	151	6046	31.9
MX PRO 1 5P5 7040.100-3M			8480	54.8	154.7	9069	47.9
MX PRO 1 5P5 7040.100-4M	AS-45M		11290	72	156.8	12092	63.8
MX PRO 1 5P5 7040.140-1M	AS-45N		3900	26.8	145.5	4150	22.7
MX PRO 1 5P5 7040.140-2M	AS-45W		7760	52.3	148.3	8299	45.4
MX PRO 1 5P5 7040.140-3M		140	11600	76.7	151.2	12449	68
MX PRO 1 5P5 7040.140-4M			15260	102	149.6	16598	90.7
MX PRO 1 5P5 7040.180-1M			4870	34.8	139.9	5227	29.6
MX PRO 1 5P5 7040.180-2M		180	9670	67.7	142.8	10453	59.1
MX PRO 1 5P5 7040.180-3M			14420	100	144.2	15680	88.7
MX PRO 1 5P5 7040.180-4M			18980	132	143.7	20906	118
MX PRO 1 5P5 7040.060-1M			1710	11.9	143.6	1847	9.4
MX PRO 1 5P5 7040.060-2M		60	3430	23	149.1	3694	18.8
MX PRO 1 5P5 7040.060-3M			5140	33.8	152	5541	28.2
MX PRO 1 5P5 7040.060-4M	AS-55M		6930	43.4	159.6	7387	37.6
MX PRO 1 5P5 7040.100-1M	AS-55N		2800	19.1	146.5	3023	16
MX PRO 1 5P5 7040.100-2M	AS-55W		5590	37.4	149.4	6046	31.9
MX PRO 1 5P5 7040.100-3M		100	8380	54.8	152.9	9069	47.9
MX PRO 1 5P5 7040.100-4M			11160	72	155	12092	63.8

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7040.140-1M	AS-65M AS-65N AS-65W	140	3860	26.8	144	4150	22.7
MX PRO 1 5P5 7040.140-2M			7670	52.3	146.6	8299	45.4
MX PRO 1 5P5 7040.140-3M			11470	76.7	149.5	12449	68
MX PRO 1 5P5 7040.140-4M			15090	102	147.9	16598	90.7
MX PRO 1 5P5 7040.180-1M		180	4820	34.8	138.5	5227	29.6
MX PRO 1 5P5 7040.180-2M			9560	67.7	141.2	10453	59.1
MX PRO 1 5P5 7040.180-3M			14260	100	142.6	15680	88.7
MX PRO 1 5P5 7040.180-4M			18760	132	142.1	20906	118
MX PRO 1 5P5 7040.060-1M		60	1650	11.9	138.6	1847	9.4
MX PRO 1 5P5 7040.060-2M			3300	23	143.4	3694	18.8
MX PRO 1 5P5 7040.060-3M			4970	33.8	147	5541	28.2
MX PRO 1 5P5 7040.060-4M			6690	43.4	154.1	7387	37.6
MX PRO 1 5P5 7040.100-1M	100	2700	19.1	141.3	3023	16	
MX PRO 1 5P5 7040.100-2M		5390	37.4	144.1	6046	31.9	
MX PRO 1 5P5 7040.100-3M		8090	54.8	147.6	9069	47.9	
MX PRO 1 5P5 7040.100-4M		10780	72	149.7	12092	63.8	
MX PRO 1 5P5 7040.140-1M	140	3720	26.8	138.8	4150	22.7	
MX PRO 1 5P5 7040.140-2M		7410	52.3	141.6	8299	45.4	
MX PRO 1 5P5 7040.140-3M		11070	76.7	144.3	12449	68	
MX PRO 1 5P5 7040.140-4M		14570	102	142.8	16598	90.7	
MX PRO 1 5P5 7040.180-1M	180	4640	34.8	133.3	5227	29.6	
MX PRO 1 5P5 7040.180-2M		9230	67.7	136.3	10453	59.1	
MX PRO 1 5P5 7040.180-3M		13770	100	137.7	15680	88.7	
MX PRO 1 5P5 7040.180-4M		18120	132	137.2	20906	118	

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.
 *RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.
 Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.
 Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.
 The characteristics of the product listed above are subjected to change without notice.

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7030.060-1M	STE-M STU-M STW SV	60	1620	11.9	136.1	1736	9.4
MX PRO 1 5P5 7030.060-2M			3270	23	142.1	3472	18.8
MX PRO 1 5P5 7030.060-3M			4920	33.8	145.5	5208	28.2
MX PRO 1 5P5 7030.060-4M			6600	43.4	152	6944	37.6
MX PRO 1 5P5 7030.100-1M		100	2660	19.1	139.2	2842	16
MX PRO 1 5P5 7030.100-2M			5330	37.4	142.5	5683	31.9
MX PRO 1 5P5 7030.100-3M			7990	54.8	145.8	8525	47.9
MX PRO 1 5P5 7030.100-4M			10640	72	147.7	11367	63.8
MX PRO 1 5P5 7030.140-1M		140	3680	26.8	137.3	3901	22.7
MX PRO 1 5P5 7030.140-2M			7300	52.3	139.5	7801	45.4
MX PRO 1 5P5 7030.140-3M			10920	76.7	142.3	11702	68
MX PRO 1 5P5 7030.140-4M			14380	102	140.9	15602	90.7
MX PRO 1 5P5 7030.180-1M		180	4600	34.8	132.1	4913	29.6
MX PRO 1 5P5 7030.180-2M			9100	67.7	134.4	9826	59.1
MX PRO 1 5P5 7030.180-3M			13590	100	135.9	14739	88.7
MX PRO 1 5P5 7030.180-4M			17890	132	135.5	19652	118
MX PRO 1 5P5 7030.060-1M	S05 S07 STA STE-S STU-S	60	1590	11.9	133.6	1736	9.4
MX PRO 1 5P5 7030.060-2M			3190	23	138.6	3472	18.8
MX PRO 1 5P5 7030.060-3M			4800	33.8	142	5208	28.2
MX PRO 1 5P5 7030.060-4M			6460	43.4	148.8	6944	37.6
MX PRO 1 5P5 7030.100-1M		100	2600	19.1	136.1	2842	16
MX PRO 1 5P5 7030.100-2M			5210	37.4	139.3	5683	31.9
MX PRO 1 5P5 7030.100-3M			7810	54.8	142.5	8525	47.9
MX PRO 1 5P5 7030.100-4M			10400	72	144.4	11367	63.8
MX PRO 1 5P5 7030.140-1M		140	3590	26.8	133.9	3901	22.7
MX PRO 1 5P5 7030.140-2M			7140	52.3	136.5	7801	45.4
MX PRO 1 5P5 7030.140-3M			10690	76.7	139.3	11702	68
MX PRO 1 5P5 7030.140-4M			14050	102	137.7	15602	90.7

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7030.180-1M			4480	34.8	128.7	4913	29.6
MX PRO 1 5P5 7030.180-2M		180	8900	67.7	131.4	9826	59.1
MX PRO 1 5P5 7030.180-3M			13290	100	132.9	14739	88.7
MX PRO 1 5P5 7030.180-4M			17480	132	132.4	19652	118
MX PRO 1 5P5 7030.060-1M		60	1630	11.9	136.9	1736	9.4
MX PRO 1 5P5 7030.060-2M			3260	23	141.7	3472	18.8
MX PRO 1 5P5 7030.060-3M			4900	33.8	144.9	5208	28.2
MX PRO 1 5P5 7030.060-4M			6590	43.4	151.8	6944	37.6
MX PRO 1 5P5 7030.100-1M		100	2660	19.1	139.2	2842	16
MX PRO 1 5P5 7030.100-2M			5310	37.4	141.9	5683	31.9
MX PRO 1 5P5 7030.100-3M			7970	54.8	145.4	8525	47.9
MX PRO 1 5P5 7030.100-4M	AS-45M		10610	72	147.3	11367	63.8
MX PRO 1 5P5 7030.140-1M	AS-45N	140	3670	26.8	136.9	3901	22.7
MX PRO 1 5P5 7030.140-2M	AS-45W		7290	52.3	139.3	7801	45.4
MX PRO 1 5P5 7030.140-3M			10900	76.7	142.1	11702	68
MX PRO 1 5P5 7030.140-4M			14340	102	140.5	15602	90.7
MX PRO 1 5P5 7030.180-1M		180	4580	34.8	131.6	4913	29.6
MX PRO 1 5P5 7030.180-2M			9090	67.7	134.2	9826	59.1
MX PRO 1 5P5 7030.180-3M			13560	100	135.6	14739	88.7
MX PRO 1 5P5 7030.180-4M			17840	132	135.1	19652	118
MX PRO 1 5P5 7030.060-1M		60	1610	11.9	135.2	1736	9.4
MX PRO 1 5P5 7030.060-2M			3220	23	140	3472	18.8
MX PRO 1 5P5 7030.060-3M			4840	33.8	143.1	5208	28.2
MX PRO 1 5P5 7030.060-4M	AS-55M		6510	43.4	150	6944	37.6
MX PRO 1 5P5 7030.100-1M	AS-55N	100	2630	19.1	137.6	2842	16
MX PRO 1 5P5 7030.100-2M	AS-55W		5250	37.4	140.3	5683	31.9
MX PRO 1 5P5 7030.100-3M			7880	54.8	143.7	8525	47.9
MX PRO 1 5P5 7030.100-4M			10490	72	145.6	11367	63.8

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7030.140-1M		140	3630	26.8	135.4	3901	22.7
MX PRO 1 5P5 7030.140-2M			7210	52.3	137.8	7801	45.4
MX PRO 1 5P5 7030.140-3M			10780	76.7	140.5	11702	68
MX PRO 1 5P5 7030.140-4M			14180	102	139	15602	90.7
MX PRO 1 5P5 7030.180-1M		180	4530	34.8	130.1	4913	29.6
MX PRO 1 5P5 7030.180-2M			8980	67.7	132.6	9826	59.1
MX PRO 1 5P5 7030.180-3M			13410	100	134.1	14739	88.7
MX PRO 1 5P5 7030.180-4M			17640	132	133.6	19652	118
MX PRO 1 5P5 7030.060-1M		60	1550	11.9	130.2	1736	9.4
MX PRO 1 5P5 7030.060-2M			3100	23	134.7	3472	18.8
MX PRO 1 5P5 7030.060-3M			4670	33.8	138.1	5208	28.2
MX PRO 1 5P5 7030.060-4M			6290	43.4	144.9	6944	37.6
MX PRO 1 5P5 7030.100-1M		100	2540	19.1	132.9	2842	16
MX PRO 1 5P5 7030.100-2M			5070	37.4	135.5	5683	31.9
MX PRO 1 5P5 7030.100-3M			7600	54.8	138.6	8525	47.9
MX PRO 1 5P5 7030.100-4M			10130	72	140.6	11367	63.8
MX PRO 1 5P5 7030.140-1M	AS-65M AS-65N AS-65W	140	3500	26.8	130.5	3901	22.7
MX PRO 1 5P5 7030.140-2M			6970	52.3	133.2	7801	45.4
MX PRO 1 5P5 7030.140-3M			10410	76.7	135.7	11702	68
MX PRO 1 5P5 7030.140-4M			13700	102	134.3	15602	90.7
MX PRO 1 5P5 7030.180-1M		180	4370	34.8	125.5	4913	29.6
MX PRO 1 5P5 7030.180-2M			8680	67.7	128.2	9826	59.1
MX PRO 1 5P5 7030.180-3M			12940	100	129.4	14739	88.7
MX PRO 1 5P5 7030.180-4M			17030	132	129	19652	118

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.
 *RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.
 Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.
 Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.
 The characteristics of the product listed above are subjected to change without notice.

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2700K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2700K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7027.060-1M	STE-M STU-M STW SV	60	1550	11.9	130.2	1662	9.4
MX PRO 1 5P5 7027.060-2M			3130	23	136	3324	18.8
MX PRO 1 5P5 7027.060-3M			4710	33.8	139.3	4986	28.2
MX PRO 1 5P5 7027.060-4M			6320	43.4	145.6	6649	37.6
MX PRO 1 5P5 7027.100-1M		100	2550	19.1	133.5	2721	16
MX PRO 1 5P5 7027.100-2M			5100	37.4	136.3	5441	31.9
MX PRO 1 5P5 7027.100-3M			7650	54.8	139.5	8162	47.9
MX PRO 1 5P5 7027.100-4M			10190	72	141.5	10883	63.8
MX PRO 1 5P5 7027.140-1M		140	3530	26.8	131.7	3735	22.7
MX PRO 1 5P5 7027.140-2M			6990	52.3	133.6	7469	45.4
MX PRO 1 5P5 7027.140-3M			10460	76.7	136.3	11204	68
MX PRO 1 5P5 7027.140-4M			13770	102	135	14938	90.7
MX PRO 1 5P5 7027.180-1M		180	4410	34.8	126.7	4704	29.6
MX PRO 1 5P5 7027.180-2M			8710	67.7	128.6	9408	59.1
MX PRO 1 5P5 7027.180-3M			13010	100	130.1	14112	88.7
MX PRO 1 5P5 7027.180-4M			17130	132	129.7	18816	118
MX PRO 1 5P5 7027.060-1M	S05 S07 STA STE-S STU-S	60	1520	11.9	127.7	1662	9.4
MX PRO 1 5P5 7027.060-2M			3060	23	133	3324	18.8
MX PRO 1 5P5 7027.060-3M			4590	33.8	135.7	4986	28.2
MX PRO 1 5P5 7027.060-4M			6180	43.4	142.3	6649	37.6
MX PRO 1 5P5 7027.100-1M		100	2490	19.1	130.3	2721	16
MX PRO 1 5P5 7027.100-2M			4990	37.4	133.4	5441	31.9
MX PRO 1 5P5 7027.100-3M			7480	54.8	136.4	8162	47.9
MX PRO 1 5P5 7027.100-4M			9950	72	138.1	10883	63.8
MX PRO 1 5P5 7027.140-1M		140	3440	26.8	128.3	3735	22.7
MX PRO 1 5P5 7027.140-2M			6840	52.3	130.7	7469	45.4
MX PRO 1 5P5 7027.140-3M			10230	76.7	133.3	11204	68
MX PRO 1 5P5 7027.140-4M			13460	102	131.9	14938	90.7

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2700K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2700K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7027.180-1M	AS-45M AS-45N AS-45W	180	4290	34.8	123.2	4704	29.6
MX PRO 1 5P5 7027.180-2M			8520	67.7	125.8	9408	59.1
MX PRO 1 5P5 7027.180-3M			12730	100	127.3	14112	88.7
MX PRO 1 5P5 7027.180-4M			16730	132	126.7	18816	118
MX PRO 1 5P5 7027.060-1M		60	1560	11.9	131	1662	9.4
MX PRO 1 5P5 7027.060-2M			3120	23	135.6	3324	18.8
MX PRO 1 5P5 7027.060-3M			4690	33.8	138.7	4986	28.2
MX PRO 1 5P5 7027.060-4M			6310	43.4	145.3	6649	37.6
MX PRO 1 5P5 7027.100-1M		100	2550	19.1	133.5	2721	16
MX PRO 1 5P5 7027.100-2M			5090	37.4	136	5441	31.9
MX PRO 1 5P5 7027.100-3M			7630	54.8	139.2	8162	47.9
MX PRO 1 5P5 7027.100-4M			10160	72	141.1	10883	63.8
MX PRO 1 5P5 7027.140-1M		140	3510	26.8	130.9	3735	22.7
MX PRO 1 5P5 7027.140-2M			6980	52.3	133.4	7469	45.4
MX PRO 1 5P5 7027.140-3M			10440	76.7	136.1	11204	68
MX PRO 1 5P5 7027.140-4M			13730	102	134.6	14938	90.7
MX PRO 1 5P5 7027.180-1M	180	4380	34.8	125.8	4704	29.6	
MX PRO 1 5P5 7027.180-2M		8700	67.7	128.5	9408	59.1	
MX PRO 1 5P5 7027.180-3M		12980	100	129.8	14112	88.7	
MX PRO 1 5P5 7027.180-4M		17080	132	129.3	18816	118	
MX PRO 1 5P5 7027.060-1M	AS-55M AS-55N AS-55W	60	1540	11.9	129.4	1662	9.4
MX PRO 1 5P5 7027.060-2M			3080	23	133.9	3324	18.8
MX PRO 1 5P5 7027.060-3M			4630	33.8	136.9	4986	28.2
MX PRO 1 5P5 7027.060-4M			6230	43.4	143.5	6649	37.6
MX PRO 1 5P5 7027.100-1M	100	2520	19.1	131.9	2721	16	
MX PRO 1 5P5 7027.100-2M		5030	37.4	134.4	5441	31.9	
MX PRO 1 5P5 7027.100-3M		7540	54.8	137.5	8162	47.9	
MX PRO 1 5P5 7027.100-4M		10040	72	139.4	10883	63.8	

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2700K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2700K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7027.140-1M		140	3470	26.8	129.4	3735	22.7
MX PRO 1 5P5 7027.140-2M			6900	52.3	131.9	7469	45.4
MX PRO 1 5P5 7027.140-3M			10320	76.7	134.5	11204	68
MX PRO 1 5P5 7027.140-4M			13580	102	133.1	14938	90.7
MX PRO 1 5P5 7027.180-1M		180	4330	34.8	124.4	4704	29.6
MX PRO 1 5P5 7027.180-2M			8600	67.7	127	9408	59.1
MX PRO 1 5P5 7027.180-3M			12840	100	128.4	14112	88.7
MX PRO 1 5P5 7027.180-4M			16890	132	127.9	18816	118
MX PRO 1 5P5 7027.060-1M		60	1490	11.9	125.2	1662	9.4
MX PRO 1 5P5 7027.060-2M			2970	23	129.1	3324	18.8
MX PRO 1 5P5 7027.060-3M			4470	33.8	132.2	4986	28.2
MX PRO 1 5P5 7027.060-4M			6020	43.4	138.7	6649	37.6
MX PRO 1 5P5 7027.100-1M		100	2430	19.1	127.2	2721	16
MX PRO 1 5P5 7027.100-2M			4850	37.4	129.6	5441	31.9
MX PRO 1 5P5 7027.100-3M			7280	54.8	132.8	8162	47.9
MX PRO 1 5P5 7027.100-4M			9700	72	134.7	10883	63.8
MX PRO 1 5P5 7027.140-1M	AS-65M AS-65N AS-65W	140	3350	26.8	125	3735	22.7
MX PRO 1 5P5 7027.140-2M			6670	52.3	127.5	7469	45.4
MX PRO 1 5P5 7027.140-3M			9960	76.7	129.8	11204	68
MX PRO 1 5P5 7027.140-4M			13110	102	128.5	14938	90.7
MX PRO 1 5P5 7027.180-1M		180	4180	34.8	120.1	4704	29.6
MX PRO 1 5P5 7027.180-2M			8310	67.7	122.7	9408	59.1
MX PRO 1 5P5 7027.180-3M			12390	100	123.9	14112	88.7
MX PRO 1 5P5 7027.180-4M			16310	132	123.5	18816	118

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.
 *RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.
 Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.
 Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.
 The characteristics of the product listed above are subjected to change without notice.

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2200K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2200K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7022.060-1M	STE-M STU-M STW SV	60	1400	11.9	117.6	1496	9.4
MX PRO 1 5P5 7022.060-2M			2820	23	122.6	2992	18.8
MX PRO 1 5P5 7022.060-3M			4240	33.8	125.4	4488	28.2
MX PRO 1 5P5 7022.060-4M			5690	43.4	131.1	5984	37.6
MX PRO 1 5P5 7022.100-1M		100	2290	19.1	119.8	2449	16
MX PRO 1 5P5 7022.100-2M			4590	37.4	122.7	4897	31.9
MX PRO 1 5P5 7022.100-3M			6890	54.8	125.7	7346	47.9
MX PRO 1 5P5 7022.100-4M			9170	72	127.3	9795	63.8
MX PRO 1 5P5 7022.140-1M		140	3180	26.8	118.6	3361	22.7
MX PRO 1 5P5 7022.140-2M			6290	52.3	120.2	6722	45.4
MX PRO 1 5P5 7022.140-3M			9410	76.7	122.6	10083	68
MX PRO 1 5P5 7022.140-4M			12390	102	121.4	13445	90.7
MX PRO 1 5P5 7022.180-1M		180	3970	34.8	114	4233	29.6
MX PRO 1 5P5 7022.180-2M			7840	67.7	115.8	8467	59.1
MX PRO 1 5P5 7022.180-3M			11710	100	117.1	12700	88.7
MX PRO 1 5P5 7022.180-4M			15410	132	116.7	16934	118
MX PRO 1 5P5 7022.060-1M	S05 S07 STA STE-S STU-S	60	1370	11.9	115.1	1496	9.4
MX PRO 1 5P5 7022.060-2M			2750	23	119.5	2992	18.8
MX PRO 1 5P5 7022.060-3M			4130	33.8	122.1	4488	28.2
MX PRO 1 5P5 7022.060-4M			5560	43.4	128.1	5984	37.6
MX PRO 1 5P5 7022.100-1M		100	2240	19.1	117.2	2449	16
MX PRO 1 5P5 7022.100-2M			4490	37.4	120	4897	31.9
MX PRO 1 5P5 7022.100-3M			6730	54.8	122.8	7346	47.9
MX PRO 1 5P5 7022.100-4M			8960	72	124.4	9795	63.8
MX PRO 1 5P5 7022.140-1M		140	3090	26.8	115.2	3361	22.7
MX PRO 1 5P5 7022.140-2M			6160	52.3	117.7	6722	45.4
MX PRO 1 5P5 7022.140-3M			9210	76.7	120	10083	68
MX PRO 1 5P5 7022.140-4M			12110	102	118.7	13445	90.7

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2200K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2200K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7022.180-1M	AS-45M AS-45N AS-45W	180	3860	34.8	110.9	4233	29.6
MX PRO 1 5P5 7022.180-2M			7670	67.7	113.2	8467	59.1
MX PRO 1 5P5 7022.180-3M			11450	100	114.5	12700	88.7
MX PRO 1 5P5 7022.180-4M			15060	132	114	16934	118
MX PRO 1 5P5 7022.060-1M		60	1400	11.9	117.6	1496	9.4
MX PRO 1 5P5 7022.060-2M			2810	23	122.1	2992	18.8
MX PRO 1 5P5 7022.060-3M			4220	33.8	124.8	4488	28.2
MX PRO 1 5P5 7022.060-4M			5680	43.4	130.8	5984	37.6
MX PRO 1 5P5 7022.100-1M		100	2290	19.1	119.8	2449	16
MX PRO 1 5P5 7022.100-2M			4580	37.4	122.4	4897	31.9
MX PRO 1 5P5 7022.100-3M			6870	54.8	125.3	7346	47.9
MX PRO 1 5P5 7022.100-4M			9140	72	126.9	9795	63.8
MX PRO 1 5P5 7022.140-1M		140	3160	26.8	117.9	3361	22.7
MX PRO 1 5P5 7022.140-2M			6290	52.3	120.2	6722	45.4
MX PRO 1 5P5 7022.140-3M			9400	76.7	122.5	10083	68
MX PRO 1 5P5 7022.140-4M			12360	102	121.1	13445	90.7
MX PRO 1 5P5 7022.180-1M	180	3940	34.8	113.2	4233	29.6	
MX PRO 1 5P5 7022.180-2M		7830	67.7	115.6	8467	59.1	
MX PRO 1 5P5 7022.180-3M		11680	100	116.8	12700	88.7	
MX PRO 1 5P5 7022.180-4M		15370	132	116.4	16934	118	
MX PRO 1 5P5 7022.060-1M	AS-55M AS-55N AS-55W	60	1390	11.9	116.8	1496	9.4
MX PRO 1 5P5 7022.060-2M			2780	23	120.8	2992	18.8
MX PRO 1 5P5 7022.060-3M			4170	33.8	123.3	4488	28.2
MX PRO 1 5P5 7022.060-4M			5610	43.4	129.2	5984	37.6
MX PRO 1 5P5 7022.100-1M	100	2270	19.1	118.8	2449	16	
MX PRO 1 5P5 7022.100-2M		4530	37.4	121.1	4897	31.9	
MX PRO 1 5P5 7022.100-3M		6790	54.8	123.9	7346	47.9	
MX PRO 1 5P5 7022.100-4M		9040	72	125.5	9795	63.8	

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 2200K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 2200K, lm)	RATED LED POWER* (Tj=85°C, W)
MX PRO 1 5P5 7022.140-1M		140	3130	26.8	116.7	3361	22.7
MX PRO 1 5P5 7022.140-2M			6210	52.3	118.7	6722	45.4
MX PRO 1 5P5 7022.140-3M			9290	76.7	121.1	10083	68
MX PRO 1 5P5 7022.140-4M			12220	102	119.8	13445	90.7
MX PRO 1 5P5 7022.180-1M		180	3900	34.8	112	4233	29.6
MX PRO 1 5P5 7022.180-2M			7740	67.7	114.3	8467	59.1
MX PRO 1 5P5 7022.180-3M			11550	100	115.5	12700	88.7
MX PRO 1 5P5 7022.180-4M			15200	132	115.1	16934	118
MX PRO 1 5P5 7022.060-1M		60	1340	11.9	112.6	1496	9.4
MX PRO 1 5P5 7022.060-2M			2670	23	116	2992	18.8
MX PRO 1 5P5 7022.060-3M			4030	33.8	119.2	4488	28.2
MX PRO 1 5P5 7022.060-4M			5420	43.4	124.8	5984	37.6
MX PRO 1 5P5 7022.100-1M		100	2190	19.1	114.6	2449	16
MX PRO 1 5P5 7022.100-2M			4370	37.4	116.8	4897	31.9
MX PRO 1 5P5 7022.100-3M			6550	54.8	119.5	7346	47.9
MX PRO 1 5P5 7022.100-4M			8730	72	121.2	9795	63.8
MX PRO 1 5P5 7022.140-1M	AS-65M AS-65N AS-65W	140	3010	26.8	112.3	3361	22.7
MX PRO 1 5P5 7022.140-2M			6000	52.3	114.7	6722	45.4
MX PRO 1 5P5 7022.140-3M			8970	76.7	116.9	10083	68
MX PRO 1 5P5 7022.140-4M			11800	102	115.6	13445	90.7
MX PRO 1 5P5 7022.180-1M		180	3760	34.8	108	4233	29.6
MX PRO 1 5P5 7022.180-2M			7480	67.7	110.4	8467	59.1
MX PRO 1 5P5 7022.180-3M			11150	100	111.5	12700	88.7
MX PRO 1 5P5 7022.180-4M			14680	132	111.2	16934	118

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.
 *RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.
 Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.
 Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.
 The characteristics of the product listed above are subjected to change without notice.